

tapes gloves work protection

technical data sheet

FRAGILE low noise opp acrylic message tape



description black "FRAGILE" font on orange bopp film with high tack acrylic adhesive **product code**: S36

specifications backing

bopp film

adhesive acrylic

total thickness 0.050mm

adhesion to steel 5.5n/25mm

standard sizes 48mm x 66m

benefits easy unwind bold font tensile strength 100n/25mm

elongation 140%

temp resistance 60°c

areas of use fragile goods carton sealing

Pomona Group Ltd PO BOX 216 Kumeu **p**: 64 9 412 6923 **f**: 64 9 412 6925 **e**: sales@pomonagroup.com

www.pomonagroup.com



tapes gloves work protection

technical data sheet

conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

tape storage

suggested storage temperature shall range between 15°c and 25°c with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as qick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.

All selfgard[™] and pomona® products are

trademarks of Pomona Group Itd and are under license in New Zealand.

Pomona Group Ltd PO BOX 216 Kumeu **p**: 64 9 412 6923 **f**: 64 9 412 6925 <u>e: sale</u>s@pomonagroup.com

www.pomonagroup.com