

tapes gloves work protection

technical data sheet

flatback paper rubber picture framing tape



description brown flatback kraft paper backing with rubber adhesive

product code: S6270

specifications

backing kraft flatback paper

adhesive rubber

total thickness 0.150mm

adhesion to steel 16n/25mm

standard sizes 24,36,48mm x 50m

benefits strong and flexible static free resistant to ink solvents tensile strength 219n/25mm

elongation 3%

temp resistance 107°c

colours brown

custom slit up to 1480mm

areas of use picture framing silkscreen printing bookbinding

Pomona Group Ltd PO BOX 216 Kumeu **p**: 64 9 412 6923 **f**: 64 9 412 6925 **e**: sales@pomonagroup.com

www.pomonagroup.com



tapes gloves work protection

technical data sheet

conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

tape storage

suggested storage temperature shall range between 15°c and 25°c with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as qick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.

All selfgard[™] and pomona® products are

trademarks of Pomona Group Itd and are under license in New Zealand.

Pomona Group Ltd PO BOX 216 Kumeu **p**: 64 9 412 6923 **f**: 64 9 412 6925 <u>e: sale</u>s@pomonagroup.com

www.pomonagroup.com